

# 3M Super 77™ Multipurpose Spray Adhesive

**Technical Data**

**March 2012**

## Product Description

A high tack, high coverage and fast drying adhesive.

## Key Features

- A high tack, high coverage fast drying, transparent adhesive for permanently attaching foils, carpeting, many lightweight foams, paper, cardboard, felt and cloth to painted or unpainted metals, wood, hardboard and other base materials.
- It provides high initial "grab" with sufficient open time to allow for positioning of materials.
- Low soak-in gives better looking and higher coverage bonds.
- Soft, non-dimpling glue lines

## Typical Properties

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

Product	3M™ Super 77™ Multipurpose Spray Adhesive	3M™ Scotch-Weld™ Super 77™ Cylinder Spray Adhesive	3M™ Super 77™ Spray Adhesive
Base:	Synthetic Elastomer	Synthetic Elastomer	Synthetic Elastomer
Solids Content - (by wt.):	25%	27%	36%
Density (lbs/gal):	6.0	6.5	6.5
Viscosity (cps):	N/A	N/A	200 - 5000
Color(s):	Translucent	Translucent	Translucent
Volatile Organic Compounds (VOC):	51%	548 g/L	504 g/L
Hazardous Air Pollutants (HAPS) % wt (calculated):	.4%	.93%	1.2%
CARB Compliant:	Yes	N/A	N/A
SCAQMD 1168 Compliant:	N/A	No	No
GREENGUARD Indoor Air Quality Certified®:	No	No	No
LEED® Eligible:	Yes	No	No
Coverage @ 1 gms /ft <sup>2</sup> per lb (sqft):	114 sqft	124 sqft	168 sqft
Spray Pattern:	Mist	Mist	Mist
Dry Time:	15 seconds – 1 minute	15 seconds – 1 minute	15 seconds – 1 minute
Bonding Range:	15 seconds – 15 minutes	15 seconds – 15 minutes	15 seconds – 15 minutes
Shear Adhesion Failure Test - SAFT <sup>(1)</sup> :	150F	150F	150F
Flammable Solvent:	Yes	Yes	Yes
Flammable Propellant:	Yes	Yes	N/A

<sup>(1)</sup>SAFT Shear Adhesion Failure Test with birch plywood, 1 inch overlap, 100 grams used, temperature start at 90F and ramped 10F every 10 mn. until complete failure.

## Available Sizes

Container Size	3M Stock Number	UPC Number
24 Fl. Oz. (Net Wt. 16.75 oz)	62-4977-4930-9	00-021200-21210-9
Large Cylinder – 29.3 lbs.	62-4979-8030-0	00-051115-25776-6
5 gallon pail – 32.5 lbs.	62-4458-8530-4	00-021200-43793-9
52 gallon drum – 338 lbs.	62-4458-9530-3	00-021200-43813-4

# 3M Super 77™ Multipurpose Spray Adhesive

---

<b>Storage</b>	Store product at 60°-80°F (16°-27°C) for maximum storage life. Higher temperatures reduce normal storage life. Lower temperatures may cause increased viscosity of a temporary nature. Rotate stock on a “first in-first out” basis.
<b>Shelf Life</b>	When stored at the recommended conditions in original, unopened container, this product has a shelf life of 15 months from date of shipment.
<b>Precautionary Information</b>	Refer to product label and Material Safety Data Sheet for health and safety information before using this product. For additional health and safety information, call 1-800-364-3577 or (651) 737-6501.
<b>Technical Information</b>	The technical information, recommendations and other statements contained in this document are based upon testes or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
<b>Product Use</b>	Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user’s method of application.
<b>Warranty, Limited Remedy, and Disclaimer</b>	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOMER OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M’s option, replacement of the 3M product or refund of the purchase price.
<b>Limitation of Liability</b>	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division  
3M Center, Building 225-3S-06  
St. Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
[www.3M.com/industrial](http://www.3M.com/industrial)

3M, Super 77 and Scotch-Weld are trademarks of 3M Company.  
The GREENGUARD INDOOR AIR QUALITY  
CERTIFIED Mark is a registered certification  
mark owned by Air Quality Sciences, Inc. and  
used under license through the Greenguard  
Environmental Institute. LEED® is a registered  
trademark of the United States Green Building Council (USGBC).  
©3M 2012